

Explosion-proof Housing

KX-AXZ103

Housing	
IP Rating	IP68, IK10, EX Protection, 6KV Surge Protection
Housing	304 Stainless steel (316L Optional)
Cooling Water	N/A
Cooling Air	N/A
Sun-Shield	YES / (Optional)
Bracket	YES / Stainless Steel 304 / 2.5 Kg / Wall or poll
EX Flexible Tube	YES / Explosion Proof Cable / 1500 mm
EX Cable Gland	YES / Explosion Proof Cable Gland
Dimension	484*410 mm



KX-AXWZ106

Housing	
IP Rating	IP68, IK10, EX Protection, 6KV Surge Protection
Housing	304 Stainless steel (316L Optional)
Cooling Water	YES / Circulate Running Water via CWT-10L (Optional)
Cooling Air	N/A
Sun-Shield	YES / (Optional)
Bracket	YES / Stainless Steel 304 / 2.5 Kg / Wall or poll
EX Flexible Tube	YES / Explosion Proof Cable / 1500 mm
EX Cable Gland	YES / Explosion Proof Cable Gland
Dimension	356*158 mm
Camera	Suitable for bullet and zoom module camera
Inner size	Φ100*270mm
Window size	Φ75mm
Window temp	≤200°C
Operation temp	-50°C+200°C
Dust concentration	≤200mg/m³
Cooling water temp	≤35°C
Cooling water flow rate	0.1°C 0.3 m3/h
Cooling water pressure	0.1Mpa
Compressed air temperature	≤35°C
Compressed air pressure	0.1- 0.3Mpa
Compressed air flow rate	0.1- 0.2/min
Power supply	AC220V/DC24V(optional)
Material	Stainless steel 304
Environment	High temperature
Inlet hole	2pcs M20x1.5"
Dimensions	351.5*153.5*182.5mm
Installation	Fixed bracket and column
Weight	10kg

