

KI-P01LM20F-SM




YEARS
SILVER
GUARANTEE



- دو سال گارانتی نقره ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها

- پشتیبانی از میکرو SD با ظرفیت 128Gb
- پشتیبانی از H.265+ / H.264
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت WDR, BLC, HLC, Defog



Camera	
Image Sensor	2MP (Sony-Japan) Progressive scan Cmos Sensor (1/2.8")
CPU	Dual-Core ARM Cortex
Lens	3.6 mm Fixed Lens @F1.6
Resolution	1920*1080 (2MP)
Available IR Range	N/A
D/N Filter	Yes-Image Algorithm
Min illumination	Color: 0.01 Lux (AGC on) - B/W: 0.001 Lux(AGC on)
Angle of View	H-FOV: 96° , V-FOV: 79° , D-FOV: 110°
Night Vision	Super Starlight Technology
Picture Adjust	
Picture Function	120dB WDR, DWDR, BLC, HLC, Defog, ROI
Shutter Speed	Manual (1/3 ~ 1/100,000), Auto
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264, H.265
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	30fps@ 2MP(1920*1080) , 30fps@ 960P
Transmission Stream	Triple Stream (Code Rate: 128 kbps-8 mbps)
Network	
Protocols	HTTPS, HTTP, TCP/IP V4-V6 , RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, NAT
Compatibility	Onvif Ver2.6 , Profile S, CGI, SDK, API
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer

Function	
Recording	FTP, NVR, CMS, VMS, SD Card
Record Type	Manual, Motion Detection, Schedule
Alarm Triggers	N/A
Event Action	Email, PTZ, Snapshot, Recording, Buzzer, Pop up, Show Message
Event	Motion Detection, Video Shelter
Intelligent Function	N/A
Interface	
Network	1 RJ45 (10M / 100M) Ethernet Port
External Audio	Audio Out, Audio in
Internal Audio	Internal Mic
Alarm	N/A
CVBS	N/A
Power	PoE LAN, DC In
Reset Button	Yes (Optional)
Memory Slot	Yes - Micro SD/SDHC/SDXC Slot (128 Gb Max)
General	
Protection Rating	IP44
Power Supply	DC12 V ± 25% (1A Max)
PoE Supply	IEEE802.3af - Max 2 Watt
Web Language	English, Persian
Dimension	31*33*33 mm
Weight	170 g
Operation Humidity	Max Up to 90%RH(Non Condensing)
Operation Temp	-35°C ~ +65°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	100K hrs min- MIL-HDBK-217F (25°)